

# EDGE

## A9



### Standard equipment



**A9 50BT**

PPL brush Ø 483 mm - 19"



**A9 55BT**

2x PPL brush  
Ø 275 mm - 10"



**A9 66BT**

2x PPL brush  
Ø 330 mm - 13"



Front squeegee blade  
L.830 mm Shore 40 Th.  
2.5 mm

Rear squeegee blade  
L.870 mm Shore 40  
Th. 3 mm

- Suitable to work for the maintenance and deep cleaning
- User friendly control panel: forward speed setting, scrubbing and vacuuming selectors, battery charge indicator, traction direction indicator, key main switch
- Large handle with traction driving lever for forward and backward directions
- Self-levelling brush plate
- Cover removable without tools provided with self-locking system
- Quick vacuum motor and filter inspection, without tools
- Detergent solution tank with large opening protected by quick locking cap
- Parking brake directly on the wheel
- Non-marking wheels
- Easy squeegee regulation without tools
- Movable shock-proof squeegee
- Hour meter and solenoid valve

	A9 50BT	A9 55BT	A9 66BT
CODE	<b>6308</b>	<b>6309</b>	<b>6310</b>
POWER SUPPLY	24V DC	24V DC	24V DC
SCRUBBING WIDTH	500mm	550mm	660mm
SQUEEGEE WIDTH	800mm	800mm	800mm
MAX WORKING CAPACITY	2250 m <sup>2</sup> /h	2475 m <sup>2</sup> /h	2970 m <sup>2</sup> /h
DETERGENT TANK CAPACITY	67L	67L	67L
RECOVERY TANK CAPACITY	77/95L	77/95L	77/95L
TRACTION TYPE	200W/automatic	200W/automatic	200W/automatic
BRUSH/VACUUM MOTOR POWER	600/450 W	600/450 W	600/450 W

**(Recommended for surfaces up to 2,200 m<sup>2</sup>)**

# Walk-behind floor scrubber dryer

## A9 50

### Optional accessories:



User friendly control panel. Speed adjustment selectors. General ON/OFF and key switch, brush and vacuum motor switch. Thermal circuit breaker to protect vacuum motor and brush motor, battery level control, hour meter.

Easy access to battery and vacuum motor compartment, without using tools. Large tank capacity, at the top in the category (67 l). 2 x 12V - 118 Ah C5 batteries to grant long work autonomy, up to 3 hours.



Control lever for brush operation and detergent water outflow. Recovery tank drain hose. Quick fitting battery charger plug.

Heavy duty 15 mm steel monobloc brush plate. Great pressure on the floor for a deep cleaning even on the toughest dirt. Self-levelling system. Solenoid valve to stop the detergent water outflow during the work interruptions.



Tubular battery Pb-acid 12V 118Ah C5



GEL Battery 12 MFP 105 12V 105Ah C5



Battery Charger 24V 25A 220-240/50-60



On-board Battery charger kit - 24V - 12A



Polyurethane front blade L.830 TH. 3

Polyurethane rear blade L.870 TH. 4



Tynex brush Ø 483 mm-19"  
Tynex brush Ø 275 mm-10"  
Tynex brush Ø 330 mm-13"

PPL 0,03 brush Ø 483 mm-19"

PPL 0,03 brush Ø 275 mm-10"

PPL 0,03 brush Ø 330 mm-13"

PES brush Ø 483 mm - 19"

PES brush Ø 275 mm-10"

PES brush Ø 330 mm-13"



EWU pad driver Ø 483mm-19"

EWU pad driver Ø 275mm-10"

EWU pad driver Ø 330mm-13"



(5 pcs package)

Ø 483 mm-19"- beige

Ø 483 mm-19"- green

Ø 483 mm-19"- black

Ø 280 mm-11"- beige

Ø 280 mm-11"- green

Ø 280 mm-11"- black

Ø 340 mm-13"- beige

Ø 340 mm-13"- green