

EDGE

HYNOX 112 (3 phase)

Entirely made of stainless steel, Hynox represents the new generation of high pressure cleaner. Designed to fully satisfy not only the operator for its ease of use, for its security systems (TSI and TQC systems) and the peculiarity of having all the features and controls at hand and at sight, but also for the maintenance technician who will have all the components immediately accessible by simply removing the cover.



Control panel

- Electric motor (hollow shaft) with thermal protector
- Triplex pump with ceramic plungers connecting rod system
- Brass head pump
- Pressure regulator with built in detergent suction
- Fuel, water and detergent filters
- 24ltr fuel tank
- Pressure gauge and thermostat
- Safety valve
- Water tank, high pressure chemical and steam valve

TSI system which includes;

- Time delayed auto stop/start 3sec delay on boiler start-up
- Stop after 1 hour of total stop
- Stop for leak detection
- Stop for lack of water
- Stop for overheating
- Warning light to advice of machine malfunction
- Burner shutdown in case of lack of fuel

Standard equipment



Gun
Lance
Nozzle
10m HP hose with
screw coupling

CODE	HYNOX 112	MAX PRESSURE		FLOW RATE	POWER HP	RPM	WATER TEMP	WEIGHT KG	DIMENSIONS LxWxH (cm)
		BAR	PSI	LTR/H					
2513	150.15	150	2.200	900	5.5	1.450	40/150	150	118x73x87
2514	200.15	200	3.000	900	7.5	1.450	40/150	150	118x73x87
2516	150.21	150	2.200	1.260	7.5	1.450	40/150	150	118x73x87
2517	200.21	200	3.000	1.260	10.0	1.450	40/150	180	118x73x87