

EDGE

LION S



Standard equipment



Lance
Gun
Nozzle
15m HP hose

Equipped with:

- Interpump high pressure pump
- In line oversized 3 ceramic pistons pump that will never operate at full capacity assuring longevity
- The pump-motor connection is by **elastic coupling**
- Rotomolded structure and stainless steel hood
- 12 Litre detergent tank
- 20 Litre water tank
- 24 Litre fuel tank
- 9 Litre antiscaler tank
- High performances S1 service electric motor that can continuously operate at full power and constant temperature (no overheating)
- the security system is assured by a **micro-switch**, a **pressure switch** and a **flow switch**
- Fuel filtration system (pre-filter, cartridge filter, self-cleaning immersion filter)
- An extremely efficient boiler (**efficiency 91%**)
- Hour meter and flame failure control

IITS system (Intelligent Timed Total Stop)

1. *Power on*
2. *Pump on* -
stop for water lack (quickly flashing light)
stop for microleaks or for 60min operating in total stop (slowly flashing light)
3. *Burner on* – burner stop by means of the flame control system with photocell (flashing light)
4. *Lack of descaler* - the light is on in case of lack of product
5. *Lack of fuel* – with burner stop



	LION S 15/200
CODE	2625
OPERATING PRESSURE	200 bar
DELIVERY RATE	15 l/min
ABS. POWER/VOLTAGE	415V~50Hz 3ph
RPM	1450
MAX. WATER TEMP.	140°C
MACHINE DIMENSIONS (cm)	94x69x110
MACHINE WEIGHT	190kg

* DIFFERENT SPECS AVAILABLE. PLEASE CONTACT US FOR MORE DETAILS.